

# Pendant/fixing rail 24/48 3m HDG

Reference 705093



Activity	Cable support systems
Product family	Support system
Brand	Wibe
Range	Accessories

## Base

Activity	Cable support systems
Product family	Support system
Brand	Wibe
Range	Accessories
GTIN	7321677050932

## Commercial and Web

Short description	Pendant/fixing rail 24/48 3m HDG
Medium description	Wibe - pendant/fixing rail 24/48 - 3m - steel hot-dip galvanized
Length	3000 mm
Material	Steel
Material type or surface treatment	Hot-dip galvanized
Corrosion class	C4

## ETIM (EC000386-Mounting rail/-profile)

Length (EF001438)	2970 mm
Width (EF000008)	48 mm
Height (EF000040)	26 mm
Slit width (EF005247)	22 mm
Material thickness (EF000386)	1.8 mm
Profile shape (EF005179)	C-profile

Model (EF000010)	Singular profile
Type of perforation (EF004147)	Back perforated
Hole width (EF005742)	9 mm
With tothing (EF000571)	No
Snap (EF007562)	No
Load bearing capacity (EF002918)	* N
Area moment of inertia I <sub>y</sub> (EF012513)	7.93 cm <sup>4</sup>
Area of inertia I <sub>z</sub> (EF012514)	2.23 cm <sup>4</sup>
Moment of resistance W <sub>y</sub> (EF012503)	3.3 cm <sup>3</sup>
Moment of resistance W <sub>z</sub> (EF012504)	1.52 cm <sup>3</sup>
Suitable for circuit integrity (EF007806)	No
Material (EF002169)	Steel
Material quality (EF001257)	*
Surface protection (EF000139)	Hot-dip galvanized
Layer thickness surface protection (EF025871)	55 µm
Colour (EF000007)	*
RAL (EF000116)	*
Weight (EF000167)	5.3 kg/m

## Logistic

Pack 1 type	Each
Quantity pack 1	1
Weight pack 1	5.3 kg
Length pack 1	2970 mm
Width pack 1	48 mm
Height pack 1	26 mm
Customs code	73089059
Net weight	5.3 kg
Country of origin	SE

## Certification

ETIM class	EC000386
------------	----------

## Status product

Product status	Commercialized
----------------	----------------

## Environmental

GWP Total A1-A3	14.787 kgCO <sub>2</sub> e
-----------------	----------------------------

For the latest information check <http://wibe-group.com/cable-support-systems/mesh-trays/vertical-pieces-and-rails/pendant-fix-rail-24-48-3m-hdg>